

Ropox StandardLine Washbasin

Pre-installation information



Electric

(40-14770, 40-14772 og 40-14773)

CONSTRUCTION

The wall must be made of a material suited for screw mounting and approved for damp rooms. The hatched area is the minimum area for reinforcement of the wall.

Tested in accordance DS/ISO 17966:2016 with the following max. user weights:

40-14772: 200kg (440 lbs)

40-14773: 200kg (440 lbs)

40-14770: 200kg (440 lbs) (when using a porcelain wash basin)

Max. tensile load of upper screws

50kg/screw (110 lbs)

The washbasin is supplied with a set of screws and rawlplugs suitable for mounting on a concrete wall. The fitter should always consider the material, condition and strength of the wall and use screws and rawlplugs suitable for the specific wall type.

PLUMBING

The drain is Ø32 (1 ¼") and ends in an Ø32x88.5° drain elbow.

The water supply ends in 2 (two) 90° shut-off valves with ½" outside thread pointing upwards (not included). The maximum protrusion of the shut-off valves and drain connection should be max 90mm (3 ½") to allow for the covers.

The optimum location and orientation is as shown in green. It is important that all hoses for water connection and drain are flexible to allow the frame to move freely within the height-adjustment range of 700-1000mm (27 1/2" – 39 2/5") (including washbasin).

For purchase of adapters for connection to various standard installations, see "Connection Adapters – Other Washbasins".

POWER

Recommended location of socket in wall for optimum and hidden wiring is shown in red. If a different location is required, the cable from the control unit is 3200mm (126").

